

PRODUCT DATA BULLETIN

Description and Typical Applications

Nuchar SA is a high-activity powdered activated carbon with large preponderance of pores in the meso and macro pore range. It is specifically designed for the adsorption of large quantities of high molecular weight substances such as color bodies. The filtering speed and acidic pH make Nuchar SA particularly effective for the treatment of corn syrups. The efficient purification of other food products, chemicals, and pharmaceuticals, and municipal and industrial wastes may also be assured with Nuchar SA. Nuchar SA meets the food-grade quality of activated carbon as defined in the current edition of the Food Chemicals Codex and is Certified NSF/ANSI Standard 61.

Specifications*

Iodine Number, (mg/g)	900 min
Molasses Decolorizing Index	14 min
Filtering Time, (sec)	50 - 100
Moisture, As Packed (%)	10 max
pH	4 - 6

Typical Properties *⊥

Apparent Density, (lbs/ cu ft)	20 - 23
Apparent Density, (kg/m ³)	320 - 370
Ash, (%)	3-6
Surface Area, (m ² /g)	1400 - 1800
Pore Volume to 1000 Å (cc/g)	1.1 - 1.3
Water Solubles (%)	1 - 3
Sieve Analysis:	
% Thru 100 mesh (150 μ)	95 - 100
% Thru 200 mesh (75 μ)	85 - 95
% Thru 325 mesh (45 μ)	65 - 85

Packaging

Bulk Trucks - Approximately 30,000 pounds	(13,608 kilograms)
Bulk Rail Cars - 80,000 - 100,000 pounds	(36,288 - 45,360 kilograms)
45-pound Bags (on nonreturnable wood pallet)	(20.4 kilograms)
Bulk Bags - 750 pounds	(340 kilograms)

*Specifications and typical property data as produced using MeadWestvaco procedures. (Rev 04 /09)

**Typical properties are for general information and are not to be construed as purchase specifications.

CAS Registry Number: 7440-44-0

The information contained herein is believed to be accurate, but no warranty is given nor is freedom from any patent to be inferred.

MWV

Specialty Chemicals
P.O. Box 140
Covington, VA 24426
FAX: (540) 965 0230

Samples: Samples are available from MeadWestvaco's Carbon Department. To request a sample, call, write or e-mail us.

Safety: Always refer to the Material Safety Data Sheet for detailed information on safety. Contact us for MSDS information.

Toll Free: 800-284-1724
Email: carbon@mwv.com

Caution: Never enter tanks or other confined areas containing wet, activated carbon. Wet, activated carbon will adsorb oxygen and asphyxiation may result.

World Wide Web:
<http://www.mwvnuharcarbon.com>

©2009 MeadWestvaco Corporation

